

Technical Data Tube Furnaces up to 1600°C

Tube Furnaces ROC 50/250/16

Max. temperature:	1600°C
Heated length:	250 mm
Temp. const. zone:	80 mm
Outer dimensions (mm):	W 665 x D 430 x H 750
Inside-Ø:	50 mm
Power:	4,0 kW
Voltage:	400 3/N V

Tube Furnaces ROC 50/450/16

Max. temperature:	1600°C
Heated length:	450 mm
Temp. const. zone:	150 mm
Outer dimensions (mm):	W 850 x D 430 x H 750
Inside-Ø:	50 mm
Power:	5,5 kW
Voltage:	400 3/N V

Tube Furnaces ROC 50/610/16

Max. temperature:	1600°C
Heated length:	610 mm
Temp. const. zone:	200 mm
Outer dimensions (mm):	W 1150 x D 430 x H 750
Inside-Ø:	50 mm
Power:	6,0 kW
Voltage:	400 3/N V

Tube Furnaces ROC 75/450/16

Max. temperature:	1600°C
Heated length:	450 mm
Temp. const. zone:	150 mm
Outer dimensions (mm):	W 850 x D 430 x H 750
Inside-Ø:	75 mm
Power:	6,5 kW
Voltage:	400 3/N V

Tube Furnaces ROC 75/610/16

Max. temperature:	1600°C
Heated length:	610 mm
Temp. const. zone:	200 mm
Outer dimensions (mm):	W 1150 x D 430 x H 750
Inside-Ø:	75 mm
Power:	7,5 kW
Voltage:	400 3/N V