

## Technical Data Tube Furnaces up to 1400°C

### Tube Furnaces ROC 50/250/14

Max. temperature:	1400°C
Heated length:	250 mm
Temp. const. zone:	80 mm
Outer dimensions (mm):	W 665 x D 430 x H 750
Inside-Ø:	50 mm
Power:	3,0 kW
Voltage:	400 3/N V

### Tube Furnaces ROC 50/450/14

Max. temperature:	1400°C
Heated length:	450 mm
Temp. const. zone:	150 mm
Outer dimensions (mm):	W 850 x D 430 x H 750
Inside-Ø:	50 mm
Power:	4,0 kW
Voltage:	400 3/N V

### Tube Furnaces ROC 50/610/14

Max. temperature:	1400°C
Heated length:	610 mm
Temp. const. zone:	200 mm
Outer dimensions (mm):	W 1150 x D 430 x H 750
Inside-Ø:	50 mm
Power:	4,5 kW
Voltage:	400 3/N V

### Tube Furnaces ROC 75/450/14

Max. temperature:	1400°C
Heated length:	450 mm
Temp. const. zone:	150 mm
Outer dimensions (mm):	W 850 x D 430 x H 750
Inside-Ø:	75 mm
Power:	5,5 kW
Voltage:	400 3/N V

### Tube Furnaces ROC 75/610/14

Max. temperature:	1400°C
Heated length:	610 mm
Temp. const. zone:	200 mm
Outer dimensions (mm):	W 1150 x D 430 x H 750
Inside-Ø:	75 mm
Power:	6,5 kW
Voltage:	400 3/N V

**Tube Furnaces ROC 105/450/14**

<b>Max. temperature:</b>	<b>1400°C</b>
<b>Heated length:</b>	<b>450 mm</b>
<b>Temp. const. zone:</b>	<b>150 mm</b>
<b>Outer dimensions (mm):</b>	<b>W 850 x D 470 x H 790</b>
<b>Inside-Ø:</b>	<b>50 mm</b>
<b>Power:</b>	<b>7,0 kW</b>
<b>Voltage:</b>	<b>400 3/N V</b>

**Tube Furnaces ROC 105/610/14**

<b>Max. temperature:</b>	<b>1400°C</b>
<b>Heated length:</b>	<b>610 mm</b>
<b>Temp. const. zone:</b>	<b>200 mm</b>
<b>Outer dimensions (mm):</b>	<b>W 1150 x D 470 x H 790</b>
<b>Inside-Ø:</b>	<b>50 mm</b>
<b>Power:</b>	<b>7,5 kW</b>
<b>Voltage:</b>	<b>400 3/N V</b>