

Technical Data Air Circulating Chamber Furnaces up to 1000l

Air Circulating Chamber Furnaces KU 40/07/A

| | |
|--------------------------|-------------------------|
| Max. temperature: | 750°C |
| Inside dimensions (mm): | W 300 x D 400 x H 300 |
| Outside dimensions (mm): | W 680 x D 1180 x H 1430 |
| Weight: | 290 kg |
| Volume: | 35 l |
| Power: | 5,2 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KU 70/07/A

| | |
|--------------------------|-------------------------|
| Max. temperature: | 750°C |
| Inside dimensions (mm): | W 350 x D 500 x H 400 |
| Outside dimensions (mm): | W 730 x D 1280 x H 1530 |
| Weight: | 360 kg |
| Volume: | 70 l |
| Power: | 10,4 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KU 140/07/A

| | |
|--------------------------|-------------------------|
| Max. temperature: | 750°C |
| Inside dimensions (mm): | W 450 x D 600 x H 500 |
| Outside dimensions (mm): | W 810 x D 1380 x H 1650 |
| Weight: | 580 kg |
| Volume: | 135 l |
| Power: | 14,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KU 270/07/A

| | |
|--------------------------|--------------------------|
| Max. temperature: | 750°C |
| Inside dimensions (mm): | W 600 x D 750 x H 600 |
| Outside dimensions (mm): | W 1040 x D 1730 x H 1800 |
| Weight: | 770 kg |
| Volume: | 270 l |
| Power: | 21,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KU 540/07/A

| | |
|--------------------------|--------------------------|
| Max. temperature: | 750°C |
| Inside dimensions (mm): | W 750 x D 900 x H 800 |
| Outside dimensions (mm): | W 1190 x D 1880 x H 2010 |
| Weight: | 920 kg |
| Volume: | 540 l |
| Power: | 28,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KU 800/07/A

| | |
|---------------------------------|---------------------------------|
| Max. temperature: | 750°C |
| Inside dimensions (mm): | W 800 x D 1250 x H 800 |
| Outside dimensions (mm): | W 1240 x D 2180 x H 2010 |
| Weight: | 1105 kg |
| Volume: | 800 l |
| Power: | 40,0 kW |
| Voltage: | 400 3/N V |