

Technical Data Air Circulating Chamber Furnaces over 1000l

Air Circulating Chamber Furnaces KT 1000/04/A

| | |
|--------------------------|--------------------------|
| Max. temperature: | 450°C |
| Inside dimensions (mm): | W 1000 x D 850 x H 1200 |
| Outside dimensions (mm): | W 1700 x D 1400 x H 1750 |
| Weight: | 670 kg |
| Volume: | 1020 l |
| Power: | 17,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KT 1500/04/A

| | |
|--------------------------|--------------------------|
| Max. temperature: | 450°C |
| Inside dimensions (mm): | W 1000 x D 850 x H 1850 |
| Outside dimensions (mm): | W 1800 x D 2100 x H 2400 |
| Weight: | 810 kg |
| Volume: | 1570 l |
| Power: | 36,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KT 2000/04/A

| | |
|--------------------------|--------------------------|
| Max. temperature: | 450°C |
| Inside dimensions (mm): | W 1100 x D 1500 x H 1200 |
| Outside dimensions (mm): | W 1900 x D 2900 x H 1750 |
| Weight: | 1100 kg |
| Volume: | 1980 l |
| Power: | 41,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KT 3000/04/A

| | |
|--------------------------|--------------------------|
| Max. temperature: | 450°C |
| Inside dimensions (mm): | W 1000 x D 1500 x H 2000 |
| Outside dimensions (mm): | W 1800 x D 2900 x H 2500 |
| Weight: | 1300 kg |
| Volume: | 3000 l |
| Power: | 48,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KT 4000/04/A

| | |
|--------------------------|--------------------------|
| Max. temperature: | 450°C |
| Inside dimensions (mm): | W 2200 x D 1500 x H 1200 |
| Outside dimensions (mm): | W 3000 x D 2900 x H 1750 |
| Weight: | 1650 kg |
| Volume: | 3960 l |
| Power: | 53,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KT 4000/04/A1

Max. temperature: 450°C
Inside dimensions (mm): W 1100 x D 1500 x H 2300
Outside dimensions (mm): W 1900 x D 2900 x H 2900
Weight: 1650 kg
Volume: 3795 l
Power: 53,0 kW
Voltage: 400 3/N V

Air Circulating Chamber Furnaces KT 5000/04/A

Max. temperature: 450°C
Inside dimensions (mm): W 2000 x D 2000 x H 1250
Outside dimensions (mm): W 2900 x D 3700 x H 1800
Weight: 1700 kg
Volume: 5000 l
Power: 66,0 kW
Voltage: 400 3/N V

Air Circulating Chamber Furnaces KT 6000/04/A

Max. temperature: 450°C
Inside dimensions (mm): W 2000 x D 2000 x H 1500
Outside dimensions (mm): W 2900 x D 3700 x H 1000
Weight: 1800 kg
Volume: 6000 l
Power: 90,0 kW
Voltage: 400 3/N V

Air Circulating Chamber Furnaces KT 8000/04/A

Max. temperature: 450°C
Inside dimensions (mm): W 2200 x D 1500 x H 2300
Outside dimensions (mm): W 3100 x D 2900 x H 2900
Weight: 1900 kg
Volume: 7590 l
Power: 96,0 kW
Voltage: 400 3/N V