

Technical Data Air Circulating Chamber Furnaces over 1000l

Air Circulating Chamber Furnaces KM 1000/06/A

| | |
|--------------------------|--------------------------|
| Max. temperature: | 650°C |
| Inside dimensions (mm): | W 1000 x D 1000 x H 1000 |
| Outside dimensions (mm): | W 1320 x D 1780 x H 1940 |
| Weight: | 1300 kg |
| Volume: | 1000 l |
| Power: | 39,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KM 1500/06/A

| | |
|--------------------------|--------------------------|
| Max. temperature: | 650°C |
| Inside dimensions (mm): | W 1500 x D 1000 x H 1000 |
| Outside dimensions (mm): | W 2020 x D 2150 x H 1750 |
| Weight: | 1500 kg |
| Volume: | 1500 l |
| Power: | 51,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KM 1500/06/A1

| | |
|--------------------------|--------------------------|
| Max. temperature: | 650°C |
| Inside dimensions (mm): | W 1000 x D 1500 x H 1000 |
| Outside dimensions (mm): | W 1520 x D 2650 x H 1750 |
| Weight: | 1500 kg |
| Volume: | 1500 l |
| Power: | 51,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KM 2000/06/A

| | |
|--------------------------|--------------------------|
| Max. temperature: | 650°C |
| Inside dimensions (mm): | W 2000 x D 1000 x H 1000 |
| Outside dimensions (mm): | W 2520 x D 2150 x H 1750 |
| Weight: | 1750 kg |
| Volume: | 2000 l |
| Power: | 75,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KM 2000/06/A1

| | |
|--------------------------|--------------------------|
| Max. temperature: | 650°C |
| Inside dimensions (mm): | W 1000 x D 2000 x H 1000 |
| Outside dimensions (mm): | W 1520 x D 2560 x H 1750 |
| Weight: | 1750 kg |
| Volume: | 2000 l |
| Power: | 75,0 kW |
| Voltage: | 400 3/N V |

Air Circulating Chamber Furnaces KM 4000/06/A

Max. temperature: 650°C
Inside dimensions (mm): W 2200 x D 1500 x H 1200
Outside dimensions (mm): W 2750 x D 2650 x H 2140
Weight: 2300 kg
Volume: 3960 l
Power: 85,0 kW
Voltage: 400 3/N V

Air Circulating Chamber Furnaces KM 4000/06/A1

Max. temperature: 650°C
Inside dimensions (mm): W 1500 x D 2200 x H 1200
Outside dimensions (mm): W 2020 x D 2850 x H 2140
Weight: 2300 kg
Volume: 4000 l
Power: 85,0 kW
Voltage: 400 3/N V