

## Technical Data High Temperature Chamber Furnaces up to 1750°C

### Chamber Furnaces HTK 16/17

Max. temperature:	1750°C
Inside dimensions (mm):	W 200 x D 300 x H 260
Volume:	15,6 l
Outside dimensions (mm):	W 820 x D 655 x H 1570
Power:	8,0 kW
Voltage:	400 3/N V
Weight:	285 kg

### Chamber Furnaces HTK 20/17

Max. temperature:	1750°C
Inside dimensions (mm):	W 250 x D 320 x H 260
Volume:	21 l
Outside dimensions (mm):	W 870 x D 675 x H 1570
Power:	8,0 kW
Voltage:	400 3/N V
Weight:	295 kg

### Chamber Furnaces HTK 40/17

Max. temperature:	1750°C
Inside dimensions (mm):	W 300 x D 350 x H 350
Volume:	37 l
Outside dimensions (mm):	W 920 x D 705 x H 1660
Power:	11,0 kW
Voltage:	400 3/N V
Weight:	375 kg

### Chamber Furnaces HTK 50/17

Max. temperature:	1750°C
Inside dimensions (mm):	W 250 x D 550 x H 350
Volume:	48 l
Outside dimensions (mm):	W 870 x D 905 x H 1660
Power:	18,0 kW
Voltage:	400 3/N V
Weight:	655 kg

### Chamber Furnaces HTK 70/17

Max. temperature:	1750°C
Inside dimensions (mm):	W 400 x D 400 x H 400
Volume:	64 l
Outside dimensions (mm):	W 1020 x D 755 x H 1710
Power:	12,0 kW
Voltage:	400 3/N V
Weight:	545 kg