

## Technical Data Drying Cabinets (natural convection)

### Drying Cabinets KTL 20/02

Max. temperature:	250°C
Inside dimensions (mm):	W 240 x D 320 x H 295
Volume:	23,0 l
Outside dimensions (mm):	W 406 x D 580 x H 604
Power:	1,0 kW
Voltage:	230 1/N V
Weight:	31 kg

### Drying Cabinets KTL 60/02

Max. temperature:	250°C
Inside dimensions (mm):	W 400 x D 390 x H 350
Volume:	55,0 l
Outside dimensions (mm):	W 620 x D 640 x H 680
Power:	1,3 kW
Voltage:	230 1/N V
Weight:	55 kg

### Drying Cabinets KTL 120/02

Max. temperature:	250°C
Inside dimensions (mm):	W 540 x D 390 x H 530
Volume:	112,0 l
Outside dimensions (mm):	W 760 x D 640 x H 860
Power:	1,9 kW
Voltage:	230 1/N V
Weight:	75 kg

### Drying Cabinets KTL 240/02

Max. temperature:	250°C
Inside dimensions (mm):	W 540 x D 540 x H 760
Volume:	221,0 l
Outside dimensions (mm):	W 760 x D 790 x H 1090
Power:	1,9 kW
Voltage:	230 1/N V
Weight:	100 kg

### Drying Cabinets KTL 400/02

Max. temperature:	250°C
Inside dimensions (mm):	W 540 x D 540 x H 1410
Volume:	411,0 l
Outside dimensions (mm):	W 760 x D 790 x H 1910
Power:	3,6 kW
Voltage:	400 3/N V
Weight:	150 kg

**Drying Cabinets KTL 700/02**

<b>Max. temperature:</b>	<b>250°C</b>
<b>Inside dimensions (mm):</b>	<b>W 940 x D 540 x H 1410</b>
<b>Volume:</b>	<b>715,0 l</b>
<b>Outside dimensions (mm):</b>	<b>W 1160 x D 790 x H 1910</b>
<b>Power:</b>	<b>4,5 kW</b>
<b>Voltage:</b>	<b>400 3/N V</b>
<b>Weight:</b>	<b>215 kg</b>