

Technical Data High Temperature Hood Furnaces

High Temperature Hood Furnaces HTH 70/18 LB

Max. temperature: 1800°C
Inside dimensions (mm): W 420 x D 420 x H 420
Volume: 70 l
Power: 24,0 kW
Voltage: 400 3/N V

High Temperature Hood Furnaces HTH 170/18 LB

Max. temperature: 1800°C
Inside dimensions (mm): W 550 x D 550 x H 550
Volume: 170 l
Power: 32,0 kW
Voltage: 400 3/N V

High Temperature Hood Furnaces HTH 300/18 LB

Max. temperature: 1800°C
Inside dimensions (mm): W 1100 x D 500 x H 550
Volume: 300 l
Power: 54,0 kW
Voltage: 400 3/N V

High Temperature Hood Furnaces HTH 500/18 LB

Max. temperature: 1800°C
Inside dimensions (mm): W 1200 x D 500 x H 800
Volume: 480 l
Power: 96,0 kW
Voltage: 400 3/N V

High Temperature Hood Furnaces HTH 1000/18 LB

Max. temperature: 1800°C
Inside dimensions (mm): W 1800 x D 700 x H 800
Volume: 1000 l
Power: 170,0 kW
Voltage: 400 3/N V

High Temperature Hood Furnaces HTH 1500/18 LB

Max. temperature: 1800°C
Inside dimensions (mm): W 2200 x D 850 x H 800
Volume: 1500 l
Power: 225,0 kW
Voltage: 400 3/N V

High Temperature Hood Furnaces HTH 2000/18 LB

Max. temperature:	1800°C
Inside dimensions (mm):	W 2400 x D 1000 x H 800
Volume:	1920 l
Power:	240,0 kW
Voltage:	400 3/N V