

Technical Data Tube Furnaces up to 1400°C

Tube Furnaces ROC 50/250/14

Max. temperature: 1400°C
Heated length: 250 mm
Temp. const. zone: 80 mm
Outer dimensions (mm): W 665 x D 430 x H 750
Inside- Ø: 50 mm
Power: 3 kW
Voltage: 400 3/N V

Tube Furnaces ROC 50/450/14

Max. temperature: 1400°C
Heated length: 450 mm
Temp. const. zone: 150 mm
Outer dimensions (mm): W 850 x D 430 x H 750
Inside- Ø: 50 mm
Power: 4 kW
Voltage: 400 3/N V

Tube Furnaces ROC 50/610/14

Max. temperature: 1400°C
Heated length: 610 mm
Temp. const. zone: 200 mm
Outer dimensions (mm): W 1150 x D 430 x H 750
Inside- Ø: 50 mm
Power: 4,5 kW
Voltage: 400 3/N V

Tube Furnaces ROC 75/450/14

Max. temperature: 1400°C
Heated length: 450 mm
Temp. const. zone: 150 mm
Outer dimensions (mm): W 850 x D 430 x H 750
Inside- Ø: 75 mm
Power: 5,5 kW
Voltage: 400 3/N V

Tube Furnaces ROC 75/610/14

Max. temperature: 1400°C
Heated length: 610 mm
Temp. const. zone: 200 mm
Outer dimensions (mm): W 1150 x D 430 x H 750
Inside- Ø: 75 mm
Power: 6,5 kW
Voltage: 400 3/N V

Tube Furnaces ROC 105/450/14

Max. temperature: 1400°C
Heated length: 450 mm
Temp. const. zone: 150 mm
Outer dimensions (mm): W 850 x D 470 x H 790
Inside- Ø: 50 mm
Power: 7 kW
Voltage: 400 3/N V

Tube Furnaces ROC 105/610/14

Max. temperature: 1400°C
Heated length: 610 mm
Temp. const. zone: 200 mm
Outer dimensions (mm): W 1150 x D 470 x H 790
Inside- Ø: 50 mm
Power: 7,5 kW
Voltage: 400 3/N V