

Technical Data Tube Furnaces up to 1500°C

Tube Furnaces ROC 50/250/15

Max. temperature: 1500°C
Heated length: 250 mm
Temp. const. zone: 80 mm
Outer dimensions (mm): W 665 x D 430 x H 750
Inside- Ø: 50 mm
Power: 3 kW
Voltage: 400 3/N V

Tube Furnaces ROC 50/450/15

Max. temperature: 1500°C
Heated length: 450 mm
Temp. const. zone: 150 mm
Outer dimensions (mm): W 850 x D 430 x H 750
Inside- Ø: 50 mm
Power: 4 kW
Voltage: 400 3/N V

Tube Furnaces ROC 50/610/15

Max. temperature: 1500°C
Heated length: 610 mm
Temp. const. zone: 200 mm
Outer dimensions (mm): W 1150 x D 430 x H 750
Inside- Ø: 50 mm
Power: 5 kW
Voltage: 400 3/N V

Tube Furnaces ROC 75/450/15

Max. temperature: 1500°C
Heated length: 450 mm
Temp. const. zone: 150 mm
Outer dimensions (mm): W 850 x D 430 x H 750
Inside- Ø: 75 mm
Power: 6 kW
Voltage: 400 3/N V

Tube Furnaces ROC 75/610/15

Max. temperature: 1500°C
Heated length: 610 mm
Temp. const. zone: 200 mm
Outer dimensions (mm): W 1150 x D 430 x H 750
Inside- Ø: 75 mm
Power: 7 kW
Voltage: 400 3/N V